

Facades / Winter gardens » Facades » MB-SR50N / SR50N HI



Facades MB-SR 50 N / MB-SR 50 N HI

Modern glass-aluminium systems distinguished by their high resistance and long-term durability.

Features

1. The possibility to achieve modern architecture of the building thanks to the shape of columns and pins that allows to build aesthetic facades with narrow dividing lines.
2. High parameters of tightness and thermal insulation.
3. Structure durability and resistance thanks to the high-quality aluminium profiles.
4. Wide application options that allows to fulfill technically advanced expectations of investors, designers and architects.
5. The possibility to make curtain walls in various shapes thanks to high static parameters of the profiles.
6. variations of interior designs, thanks to a number of different glazing types, e.g. anti-reflective , safety glass.
7. Wide range of RAL colours gives You freedom in shaping the facades.

Technical data

Glass	The possibility to apply glass with enhanced sound insulation, tempered, safety, anti-burglary, ornament and solar protective.
Colour range	According to the RAL color range and wood-grain coating from Aluprof ColorCollection
Gaskets	EPDM
Spacer frame	In standard there is steel galvanized frame. Optionally Swisspacer Ultimate available in various colour options.
Profile	The width of columns and bolts up to 50 mm, and the installation depth adopted to construction loads of the building; profile structure compatible with other window and door systems; application of a continuous thermal separator, and for MB-SR50 N HI profiles additionally a special insulating insert inside the section and the under window space.